

Conti Hybrid HT3

Fuel-Efficient, Spread Axle Trailer

Advanced tread compound

to achieve performance in high scrub application and still maintain low rolling resistance.

Patented groove technology

for minimal stone retention, extending casing life.



Pyramidal stone ejection

system integrated into the center groove for added casing protection.

Conti Hybrid HT3

Fuel-Efficient Spread Axle Trailer

Advanced tread compound to achieve performance in high scrub application and still maintain low rolling resistance.

Patented groove technology for minimal stone retention, extending casing life.

Pyramidal stone ejection system integrated into the center groove for added casing protection.

Superior performance in spread-axle trailer applications vs. HSR2. *Based on projected calculations.



Key Features



SmartWay® Verified



Retread Available




Available in 19.5"



Recommended Application

Long Haul and Regional



Compares to

Michelin: XTE, XTE 2, X Multi Energy T2

Bridgestone: R196A, R250F

Goodyear: Endurance RST

Product Data — Conti Hybrid HT3

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)	Static Loaded Radius		Overall Inflated Diameter		Overall Inflated Width		Loaded Section Width		Approved Rim(s)	Minimum Dual Spacing		Revs Per Unit		Tire Weight		Max. Load @ Inflation	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	Single	Dual
255/70R22.5	H	05311030000 05655430000	16	75	17.2	437	36.6	928	9.9	252	10.7	271	7.50, 8.25	11.3	287	566	352	89	41	5510, 120 (2500, 830)	5070, 120 (2300, 830)
11R22.5	G	05321060000 05651000000	16	75	19.2	488	41.2	1046	11.1	282	12.0	305	8.25	12.5	318	502	312	111	50	6175, 105 (2800, 720)	5840, 105 (2650, 720)
11R22.5	H	05323060000 05655740000	16	75	19.2	488	41.2	1046	11.1	282	12.0	305	8.25	12.5	318	502	312	113	51	6610, 120 (3000, 830)	6005, 120 (2725, 830)
295/75R22.5	G	05321040000 05651650000	16	75	18.5	470	39.6	1006	11.1	282	12.6	320	8.25	12.5	318	523	325	107	49	6175, 110 (2800, 760)	5675, 110 (2575, 760)
11R24.5	H	05321260000 05651190000	16	75	20.2	513	43.1	1095	11.1	282	12.0	305	8.25	12.5	318	480	298	122	55	7160, 120 (3250, 830)	6610, 120 (3000, 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

■ STANDARD ARTICLE

■ INTELLIGENT ARTICLE

Note: Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. These specifications subject to change without notice. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.